



AVONMORE

AVONMORE is a classic multi-rail design that is available in an ELECTRIC or HYDRONIC option. Its range of sizes, finishes, and straight or curved models makes it an extremely popular specification product for new build. It is highly functional for heating, with good outputs, and it has tube spacing for practical towel placement. With three different rail configurations, this is a flexible choice for any project.



Electric (PUR-EECOS125)
in Chrome



Hydronic (PUR-COS86)
in White

**ELECTRIC &
HYDRONIC**



MYSON 
comfort delivered by PURMO

ELECTRIC

HYDRONIC

| MODEL | Height (H) (inch) | Width (W) (inch) | Electric Weight (lb) | Hydronic Weight (lb) | A (inch) | B (inch) | C (inch) | D (inch) | E** (inch) | F** (inch) |
|-------|----------------------|---------------------|-------------------------|-------------------------|-------------|-------------|-------------|-------------|---------------|---------------|
| 85 | 33 15/16" | 19 1/16" | 40 | 39 | 17 15/16" | 20 3/16" | 38 7/8" | 35 1/16" | 26 1/16" | 3 1/16" |
| 86 | 33 15/16" | 23 5/8" | 45 | 45 | 21 1/4" | 24 1/4" | 38 7/8" | 35 1/16" | 26 1/16" | 3 1/16" |
| 125 | 48 1/8" | 19 1/16" | 60 | 59 | 17 15/16" | 20 3/16" | 53 1/16" | 49 3/4" | 33 1/16" | 7 1/4" |
| 126 | 48 1/8" | 23 5/8" | 70 | 68 | 21 1/8" | 24 1/8" | 53 1/16" | 49 3/4" | 33 1/16" | 7 1/4" |

125, 126
 85, 86

**Dimensions E and F may vary depending on the positioning of the mounting brackets.

General Specifications

CERTIFICATION
Produced in a ISO 4001:2004 certified facility.
Manufactured and 3rd party tested by ETL according to UL-499 and CAN/CSA-E60335-2-43.

WARRANTY
5 year guarantee from date of purchase to the original owner against manufacturing defects. Visit our website for warranty details.

SYSTEM
MYSON hydronic towel warmers are for properly designed **closed loop** (**not open loop and/or drinking water systems**) hydronic heating systems in residential and commercial applications.

CONNECTIONS
4 x 1/2" BSP as standard. Valves and fittings are available as a separately purchased option (refer to page 28 in 2026 product guide).

AIR VENTS & PLUG
Included in the packaging installed for Hydronic version.

OPERATING PARAMETERS
Maximum sustained working pressure is 77psi. Maximum sustained temperature is 230°F.

MATERIAL
AVONMORE towel warmers are produced with cold-rolled steel tube. Profile 1" round tubes.

ACCESSORIES
Please refer to page 28, 29 in 2026 product guide for complete listing of available accessories.

FINISH OPTIONS

HEATING FLUID
Electric towel warmers are filled with non-toxic glycol based fluid to facilitate heat transfer.

APM® TECHNOLOGY
APM® represents the most advanced element technology available. It is an economical, self-regulating element. When it reaches the required temperature, it reduces power consumption accordingly. There is no need for a thermostat.

Heat Outputs

| ORDER CODE | | | | Stock Finishes | Special Order Finishes | Hydronic Heat Outputs @ AT 180°F | | Hydronic Heat Outputs @ AT 140°F | | Electric Heat Outputs | | | |
|----------------------------|-------------|-------------|-------------|----------------|------------------------|----------------------------------|-------|----------------------------------|------|-----------------------|------|--|--|
| Straight | | Curved | | | | Btu/h | Btu/h | PL* | PA** | PL* | PA** | | |
| Order Code | Legacy Code | Order Code | Legacy Code | | | Watts | Amps | | | | | | |
| AVONMORE - Hydronic | | | | | | | | | | | | | |
| PUR-COS85 | COS85 | PUR-COC85 | COC85 | WH, CH, BN, MB | NI, ORB | 1,300 | 1,951 | 582 | 585 | N/A | | | |
| PUR-COS86 | COS86 | PUR-COC86 | COC86 | WH, CH, BN, MB | NI, ORB | 1,538 | 2,273 | 690 | 695 | N/A | | | |
| PUR-COS125 | COS125 | PUR-COC125 | COC125 | WH, CH, BN, MB | NI, ORB | 1,857 | 2,710 | 828 | 827 | N/A | | | |
| PUR-COS126 | COS126 | PUR-COC126 | COC126 | WH, CH, BN, MB | NI, ORB | 2,188 | 3,159 | 984 | 988 | N/A | | | |
| AVONMORE - Electric | | | | | | | | | | | | | |
| PUR-ECOS85 | ECCOS85 | PUR-ECOC85 | ECOC85 | WH, CH, BN, MB | NI, ORB | | | | | 200 | 1.75 | | |
| PUR-ECOS86 | ECCOS86 | PUR-ECOC86 | ECOC86 | WH, CH, BN, MB | NI, ORB | | | | | 200 | 1.75 | | |
| PUR-ECOS125 | ECCOS125 | PUR-ECOC125 | ECOC125 | WH, CH, BN, MB | NI, ORB | | | | | 300 | 2.73 | | |
| PUR-ECOS126 | ECCOS126 | PUR-ECOC126 | ECOC126 | WH, CH, BN, MB | NI, ORB | | | | | 300 PL | 2.73 | | |
| | | | | | | | | | | 400 PA | 3.63 | | |

NOTE: Be sure to include the FINISH suffix at the end of the order code when placing your order. **PA= Painted Finish *PL= Plated Finish

Electric Specifications

800-501-7697

www.purmoUSA.com

MYSON 
comfort delivered by PURMO